

Application/Control Number: 09/960,743

Page 2

Art Unit: 2821

CLMPTO

09/24/2001

D.BROWN

08/25/2004

**BEST AVAILABLE COPY**

1. A magnetization reversal method of applying an external magnetic field to a magnetoresistive film;

wherein said magnetoresistive film has a structure in which a nonmagnetic film is placed between magnetic films with an easy axis of magnetization along a perpendicular direction to a film plane and wherein said external magnetic field comprises magnetic fields from a plurality of directions including a direction of the easy axis of magnetization of said magnetic films.

2. The magnetization reversal method according to Claim 1, wherein said magnetic field applied in said direction of the easy axis of magnetization comprises magnetic fields applied by a plurality of magnetic field applying means.

3. The magnetization reversal method according to Claim 1, wherein said magnetoresistive film further comprises a magnetic layer with greater longitudinal magnetic anisotropy than that of said magnetic films, between said magnetic film and the nonmagnetic film.

4. The magnetization reversal method according to Claim 3, wherein said magnetic film and said magnetic layer with greater longitudinal magnetic anisotropy are exchange-coupled with each other.

5. The magnetization reversal method according to Claim 1, wherein said nonmagnetic layer is an insulator.

6. The magnetization reversal method according to Claim 1, wherein said external magnetic field comprises magnetic fields generated by electric currents flowing in conductor lines.

7. A magnetization reversal method of applying a magnetic field from outside to a magnetic film to change a direction of magnetization, wherein magnetic fields are applied from a plurality of directions to said magnetic film and intensities of the respective magnetic fields are varied to effect reversal of magnetization in said magnetic film.

8. The magnetization reversal method according to Claim 7, wherein at least one magnetic field is a first magnetic field applied with variation in intensity during a period of complete reversal of magnetization in said magnetic film and another magnetic field is a second magnetic field applied in a fixed intensity and thereafter retained in the intensity of the magnetic field during the period of complete reversal of magnetization in said magnetic film.

9. The magnetization reversal method according to Claim 7, wherein an easy axis of magnetization of said magnetic film is a perpendicular direction to a film plane.

10. The magnetization reversal method according to Claim 7, wherein said magnetic film has a structure in which a nonmagnetic layer is placed between a plurality of magnetic layers.

11. The magnetization reversal method according to Claim 10, wherein said magnetic film is a magnetoresistive film.

12. The magnetization reversal method according to Claim 10, wherein said magnetic layer has an easy axis of magnetization along a perpendicular direction to a film plane.

13. The magnetization reversal method according to Claim 12, wherein a magnetic layer with greater longitudinal magnetic anisotropy than that of said magnetic layers is further placed between said magnetic layer and said nonmagnetic layer.

14. The magnetization reversal method according to Claim 8, wherein said second magnetic field is

Art Unit: 2821

applied in a direction of easy magnetization of said magnetic film.

15. The magnetization reversal method according to Claim 14, wherein said plurality of applying directions of the magnetic fields include a direction inclined from the direction of easy magnetization of said magnetic film, the magnetic fields are simultaneously applied in the direction of easy magnetization of said magnetic film and in the direction inclined from the easy axis of magnetization, the application of the magnetic field in the direction inclined from the easy axis of magnetization is first stopped, and thereafter the application of the magnetic field in the direction of easy magnetization is stopped.

16. The magnetization reversal method according to Claim 7, wherein said magnetic fields are magnetic fields generated by electric currents flowing in conductor lines.

17. A magnetization reversal method of applying a magnetic field from outside to a magnetic film with an easy axis of magnetization along a perpendicular direction to a film plane to change a direction of magnetization, wherein said magnetic field applied is a

Art Unit: 2821

magnetic field from a direction inclined from the easy axis of magnetization of said magnetic film.

18. The magnetization reversal method according to Claim 17, wherein said magnetic film is a magnetoresistive film in which a nonmagnetic layer is placed between a plurality of magnetic layers.

19. The magnetization reversal method according to Claim 17, wherein said magnetic field is a magnetic field generated by an electric current flowing in a conductor line.

20. A magnetoresistive film comprising a first magnetic film and a second magnetic film with an easy axis of magnetization along a perpendicular direction to a film plane, and having a structure in which a nonmagnetic layer is placed between said first magnetic film and second magnetic film.

wherein a magnetization reversal magnetic field of said first magnetic film < a magnetization reversal magnetic field of said second magnetic film, and wherein said second magnetic film undergoes reversal of magnetization by simultaneously applying the magnetization reversal magnetic field of said first magnetic film and a magnetic field inclined from the easy axis of magnetization.

21. The magnetoresistive film according to Claim 20, wherein a direction of the magnetic field inclined from the easy axis of magnetization is a longitudinal direction in the film plane of said magnetic film.

22. The magnetoresistive film according to Claim 20, further comprising a magnetic layer with greater longitudinal magnetic anisotropy than that of said second magnetic film, between said second magnetic film and said nonmagnetic layer.

23. The magnetoresistive film according to Claim 22, wherein said magnetic layer and said magnetic layer with greater longitudinal magnetic anisotropy are exchange-coupled with each other.

24. The magnetoresistive film according to Claim 20, wherein said first and/or second magnetic film is a ferrimagnetic material.

25. A magnetoresistive film comprising a first magnetic film and a second magnetic film with an easy axis of magnetization along a perpendicular direction to a film plane, and having a structure in which a nonmagnetic film is placed between said first magnetic film and said second magnetic film.

wherein said first magnetic film undergoes

Art Unit: 2821

reversal of magnetization by applying a magnetic field in a direction of the easy axis of magnetization and a magnetic field in a direction inclined from the easy axis of magnetization, and wherein said second magnetic film does not undergo reversal of magnetization by the magnetic fields applied to said first magnetic film.

26. The magnetoresistive film according to Claim 25, wherein the magnetic field in the direction inclined from the easy axis of magnetization is applied in a longitudinal direction in the film plane of said magnetic film.

27. The magnetoresistive film according to Claim 25, further comprising a magnetic layer with greater longitudinal magnetic anisotropy than that of said first magnetic film, between said first magnetic film and said nonmagnetic film.

28. The magnetoresistive film according to Claim 27, wherein said first magnetic film and said magnetic layer with greater longitudinal magnetic anisotropy are exchange-coupled with each other.

29. The magnetoresistive film according to Claim 25, wherein said first and/or second magnetic film is a ferrimagnetic material.



Art Unit: 2821

30. A magnetic memory comprising:

a substrate;

a magnetoresistive film provided on the substrate, which has a structure in which a nonmagnetic layer is placed between a plurality of magnetic films with an easy axis of magnetization along a perpendicular direction to a film plane;

a write line for applying a magnetic field to said magnetoresistive film; and

a bit line provided on the opposite side to said substrate with respect to the magnetoresistive film,

wherein magnetization in at least one magnetic film of said magnetoresistive film is reversed by magnetic fields generated by electric currents flowing in said write line and in said bit line.

31. A magnetic memory comprising:

a substrate;

a magnetoresistive film provided on the substrate, which has a structure in which a nonmagnetic layer is placed between a plurality of magnetic films with an easy axis of magnetization along a perpendicular direction to a film plane;

a write line for applying a magnetic field to said magnetoresistive film; and

a bit line provided on the opposite side to said substrate with respect to the magnetoresistive film.

wherein the magnetic field from said write line is applied in a direction of the easy axis of magnetization of said magnetic films of said magnetoresistive film and a magnetic field from said bit line is applied in a direction inclined from the easy axis of magnetization.

32. The magnetic memory according to Claim 30 or 31, wherein said nonmagnetic film is an insulator.

33. The magnetic memory according to Claim 30 or 31, wherein said write line is shared between adjacent magnetoresistive films.

34. The magnetic memory according to Claim 30 or 31, further comprising a magnetic layer with greater longitudinal magnetic anisotropy than that of said magnetic film, between said magnetic film and nonmagnetic layer.

35. The magnetic memory according to Claim 34, wherein said magnetic film and said magnetic layer with greater longitudinal magnetic anisotropy are exchange-coupled with each other.

36. (Amended) The magnetic memory according to either one of Claims 30 and 31, wherein said magnetoresistive film is a magnetoresistive film in which at least one magnetic film undergoes reversal of magnetization by a magnetic field in a direction of the easy axis of magnetization and in which another magnetic film undergoes reversal of magnetization by applying both the magnetic field in the direction of the easy axis of magnetization and the magnetic field inclined from the direction of the easy axis of magnetization,

wherein recording of information is implemented by applying the magnetic field in the direction of the easy axis of magnetization and the magnetic field in the direction inclined from the direction of the easy axis magnetization, and reproduction of information is implemented by applying only the magnetic field in the direction of the easy axis of magnetization.

37. (Amended) The magnetic memory according to either one of Claims 30 and 31, wherein said magnetoresistive film is a magnetoresistive film in which at least one magnetic film undergoes reversal of magnetization by applying the magnetic fields in the direction of the easy axis of magnetization and in the direction inclined from the direction of the easy axis of magnetization and in which another magnetic film does not undergo reversal of magnetization even by applying the same magnetic fields,

wherein recording and/or reproduction of information is implemented by applying the magnetic fields in the direction of the easy axis of magnetization and in the direction inclined from the easy axis of magnetization.

38. The magnetic memory according to Claim 30 or 31, wherein a plurality of magnetoresistive films are arrayed in a matrix pattern on said substrate.

39. The magnetic memory according to Claim 38, wherein during recording of information, electric currents are made to flow in said bit line and in said write line to apply magnetic fields, thereby selecting a magnetoresistive film.

40. The magnetic memory according to Claim 39, wherein the bit line for selection of the magnetoresistive film is a bit line connected to an adjacent magnetoresistive film.

41. The magnetic memory according to Claim 39, wherein the bit line for selection of the magnetoresistive film is a bit line connected to the magnetoresistive film to be selected.

42. The magnetic memory according to Claim 39, wherein the magnetic field from said bit line has a

longitudinal component in the film plane of said magnetoresistive film.

43. The magnetic memory according to Claim 39, wherein the magnetic field from said bit line has a component along the direction of the easy axis of magnetization of said magnetoresistive film.

44. The magnetic memory according to Claim 39, further comprising a transistor connected to said magnetoresistive film.

45. The magnetic memory according to Claim 44, wherein said magnetoresistive film is formed immediately above a drain region of said transistor.

46. The magnetic memory according to Claim 45, wherein a source electrode line connected to a source region of said transistor also serves as said write line.

47. A magnetic memory comprising:

a substrate;

a magnetoresistive film formed on the substrate, which has a structure in which a nonmagnetic layer is placed between magnetic films with an easy axis of magnetization along a perpendicular direction to a film

Art Unit: 2821

plane;

a write line for applying a magnetic field to said magnetoresistive film; and

a bit line provided on the opposite side to said substrate with respect to said magnetoresistive film,

said magnetic memory comprising means for applying an external magnetic field to the magnetic films of said magnetoresistive film while varying an intensity or a direction of the external magnetic field.

48. The magnetic memory according to Claim 47, wherein said nonmagnetic film is an insulator.

49. The magnetic memory according to Claim 47, wherein said write line is shared between adjacent magnetoresistive films.

50. The magnetic memory according to Claim 47, wherein said magnetoresistive film is placed so that magnetic fields from said write line and bit line are applied in the direction of the easy axis of magnetization and in a direction inclined from the direction of the easy axis of magnetization to said magnetoresistive film.

51. The magnetic memory according to Claim 50, further comprising a magnetic layer with greater

longitudinal magnetic anisotropy than that of said magnetic film, between said magnetic film and nonmagnetic layer.

52. The magnetic memory according to Claim 51, wherein the direction inclined from the easy axis of magnetization is a longitudinal direction in the film plane of said magnetic film and wherein during recording of information, application of the magnetic field in the longitudinal direction is first stopped and thereafter the application of the magnetic field in the direction of the easy axis of magnetization is stopped.

53. A magnetic memory comprising:

a substrate;

magnetoresistive films formed in a matrix pattern on the substrate;

a write line for applying a magnetic field to said magnetoresistive films; and

a bit line provided on the opposite side to said substrate with respect to said magnetoresistive films.

wherein in said magnetoresistive films, a first magnetic film, a second magnetic film, a nonmagnetic film, a third magnetic film, and a fourth magnetic film are stacked in the order named, at least the first and fourth magnetic films have their easy axis of

Art Unit: 2821

magnetization along a perpendicular direction to a film plane, and said second and third magnetic films have greater longitudinal magnetic anisotropy than that of said first and second magnetic films.

wherein at the same time as the magnetic field is applied in a direction of easy magnetization of said first and second magnetic films from said write line, a magnetic field is applied in a direction inclined from the easy axis of magnetization from said bit line, thereby selecting a specific magnetoresistive film.

54. A magnetic memory comprising:

a substrate, and a plurality of magnetoresistive films formed in a matrix pattern on the substrate, said magnetoresistive films each having a structure in which a nonmagnetic layer is placed between magnetic films with an easy axis of magnetization along a perpendicular direction to a film plane;

a write line for applying a magnetic field to said magnetoresistive films; and

a bit line on the opposite side to said substrate with respect to said magnetoresistive films,

wherein the magnetic field from said write line and a magnetic field from said bit line are simultaneously applied, application of the magnetic field from the bit line is first stopped, and thereafter application of the magnetic field from the



Art Unit: 2821

write line is stopped after magnetization of said magnetoresistive films has been aligned in the direction of the magnetic field from said write line, thereby implementing recording or reproduction of information.

--55. (New) The magnetic memory according to Claim 34, wherein said magnetoresistive film is a magnetoresistive film in which at least one magnetic film undergoes reversal of magnetization by a magnetic field in a direction of the easy axis of magnetization and in which another magnetic film undergoes reversal of magnetization by applying both the magnetic field in the direction of the easy axis of magnetization and the magnetic field inclined from the direction of the easy axis of magnetization,

wherein recording of information is implemented by applying the magnetic field in the direction of the easy axis of magnetization and the magnetic field in the direction inclined from the direction of the easy axis magnetization, and reproduction of information is implemented by applying only the magnetic field in the direction of the easy axis of magnetization.

56. (New) The magnetic memory according to Claim 34, wherein said magnetoresistive film is a magnetoresistive film in which at least one magnetic film undergoes reversal of magnetization by applying the magnetic fields in the direction of the easy axis of magnetization and in the direction inclined from the direction of the easy axis of magnetization and in which another magnetic film does not undergo reversal of magnetization even by applying the same magnetic fields,

wherein recording and/or reproduction of information is implemented by applying the magnetic fields in the direction of the easy axis of magnetization and in the direction inclined from the easy axis of magnetization.--.

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☒ OTHER: small letter

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**